

## MSC-3000 and MSC-6000, Centrifuge/Vortex Multi-Spins

Centrifuge/vortex Multi-Spins **MSC-3000** and **MSC-6000** are products of many years evolution of Spin-Mix-Spin technology that is intended for collecting micro volumes of reagents on the micro-tube's bottom (first centrifugation spin), following mixing (mix) and collecting the reagents again from the walls and cap of the microtube (second spin). We named this repetitive algorithm of operation that is aimed at reducing the mistakes during sample preparation for PCR analysis a "sms-algorithm".

Multi-Spin is a fully automatic device for reproducing sms-algorithm for 12 tubes at one time, thus saving time considerably. A must-have instrument for PCR and DNA analyses laboratory. Multi Spin is four devices combined in one:

1. Centrifuge — Maximum RCF:  
**MSC-3000:** up to  $800 \times g$   
**MSC-6000:** up to  $2,350 \times g$
2. Vortex (3 mixing modes — **soft, medium, hard**; regulated time; Vortexing regulation timer 1–20 sec)
3. Centrifuge/Vortex;
4. SMS-cycler for realization of the "sms-algorithm".

MSC-6000



MSC-3000



2 ×  Both product video is available on the website

### Comparison of FVL-2400N, MSC-3000 and MSC-6000

Multi-Spin allows considerable time saving compared to Combi-Spin by automatically performing cycling program of sample mixing and spinning according to the set spin-mix-spin cycle for 12 microtubes simultaneously.

FVL-2400N

MSC-3000

MSC-6000



Specifications:	FVL-2400N	MSC-3000	MSC-6000
Speed control range max.	2,800 rpm	3,500 rpm	6,000 rpm
RCF max.	700×g	800×g	2,350×g
Number of tubes vortexing	1 individually	12 simultaneously	
Time for completing “spin-mix-spin” cycle:			
for 2 microtubes	60 sec	25 sec	15 sec
for 12 microtubes	5–6 min	1 min 30 sec	1 min
for 100 microtubes	60 min	15 min	10 min
Unit price ratio	1×	1.6×	1.7×

## MSC-3000 and MSC-6000, Centrifuge/Vortex Multi-Spins

Specifications	MSC-3000	MSC-6000
Speed regulation range (increment 100 rpm)	1,000–3,500 rpm	1,000–6,000 rpm
RCF max.	800 × g	2,350 × g
Spin timer	1 sec–99 min	1 sec–30 min
Vortexing intensity	Soft, medium, hard	
Vortexing time	0–20 sec (increment 1 sec)	
SMS–cycle regulation	1–999 cycles	
Display	LCD, 2 × 16 signs	
Safety	Autostop at open lid	Lid lock
Overall dimensions (W × D × H)	190 × 235 × 125 mm	
Weight	2.1 kg	2.5 kg
Input current/power consumption	12 V, 11 W (0.9 A)	24 V, 24 W (1 A)
External power supply	Input AC 100–240 V 50/60 Hz, Output DC 12 V	Input AC 100–240 V 50/60 Hz, Output DC 24 V

### Rotor R-1.5



#### Catalogue number:

**MSC-3000** with standard rotors R-1.5, R-0.5/0.2 BS-010205-AAN

**MSC-6000** with standard rotors R-1.5, R-0.5/0.2 BS-010211-AAL

### Interchangeable rotors for MSC-3000 and MSC-6000

Platform	Description	Capacity	Type	Cat. Number
❶ R-0.5/0.2	12 × 0.5 ml and 12 × 0.2 ml microtubes	24	Standard	BS-010205-BK
❷ R-1.5	12 × 1.5 ml microtubes	12	Standard	BS-010205-AK
❸ R-2/0.5	8 × 2.0 ml and 8 × 0.5 ml microtubes	16	Optional	BS-010205-CK
❹ R-2/0.5/0.2	6 × 2.0 ml, 6 × 0.5 ml and 6 × 0.2 ml microtubes	18	Optional	BS-010205-DK
❺ SR-16	Two 8-section strips for 0.2 ml microtubes	16	Optional	BS-010202-AK

❶ R-0.5/0.2



❷ R-1.5



❸ R-2/0.5



❹ R-2/0.5/0.2



❺ SR-16



Gentaur Molecular Products  
Voortstraat 49  
1910 Kampenhout, BELGIUM

Tel 0032 16 58 90 45 | Fax 0032 16 50 90 45  
www.gentaur-worldwide.com  
info@gentaur.com